



## JAW & EYE TURNBUCKLES

- Drop forged.
- Hot dipped galvanized.
- Jaw on sizes 1/4" to 5/8" are fitted with nuts and bolts. 3/4" and larger are fitted with pin and cotter.
- Meets design and performance requirements of ASTM F 1145 Class H.
- See Warnings "Turnbuckles" on Page 8 for proper use and selection.

Indusco Part #	Threaded Dia. x Take-up	A	B	F Closed	H	I	W	Weight Each	Working Load Limit*
939 00016	1/4 x 4	.78	.34	7.35	.45	.62	4.00	.32	500
939 00051	5/16 x 4-1/2	.94	.44	8.71	.50	.72	4.50	.47	800
939 00096	3/8 x 6	1.12	.53	10.81	.54	.87	6.00	.86	1,200
939 00146	1/2 x 6	1.44	.72	12.29	.65	1.06	6.00	1.54	2,200
939 00176	1/2 x 9	1.44	.72	15.29	.65	1.06	9.00	1.95	2,200
939 00201	1/2 x 12	1.44	.72	18.29	.65	1.06	12.00	2.19	2,200
939 00236	5/8 x 6	1.75	.88	13.74	.79	1.31	6.00	2.81	3,500
939 00266	5/8 x 9	1.75	.88	16.74	.79	1.31	9.00	3.01	3,500
939 00291	5/8 x 12	1.75	.88	19.74	.79	1.31	12.00	3.32	3,500
939 00326	3/4 x 6	2.09	1.00	15.19	.94	1.50	6.00	4.00	5,200
939 00356	3/4 x 9	2.09	1.00	18.19	.94	1.50	9.00	4.98	5,200
939 00386	3/4 x 12	2.09	1.00	21.19	.94	1.50	12.00	5.36	5,200
939 00416	3/4 x 18	2.09	1.00	27.19	.94	1.50	18.00	7.00	5,200
939 00461	7/8 x 12	2.38	1.25	22.34	1.13	1.75	12.00	8.75	7,200
939 00486	7/8 x 18	2.38	1.25	28.34	1.13	1.75	18.00	10.60	7,200
939 00495	1 x 6	3.00	1.44	18.34	1.34	2.06	6.00	8.92	10,000
939 00521	1 x 12	3.00	1.44	24.34	1.34	2.06	12.00	11.20	10,000
939 00551	1 x 18	3.00	1.44	30.34	1.34	2.06	18.00	14.10	10,000
939 00581	1 x 24	3.00	1.44	36.34	1.34	2.06	24.00	16.80	10,000
939 00611	1-1/4 x 12	3.56	1.81	26.82	1.75	2.81	12.00	20.00	15,200
939 00626	1-1/4 x 18	3.56	1.81	32.82	1.75	2.81	18.00	24.20	15,200
939 00647	1-1/4 x 24	3.56	1.81	38.82	1.75	2.81	24.00	28.10	15,200
939 00666	1-1/2 x 12	4.06	2.12	28.50	2.06	2.81	12.00	30.00	21,400
939 00686	1-1/2 x 18	4.06	2.12	34.50	2.06	2.81	18.00	35.00	21,400
939 00701	1-1/2 x 24	4.06	2.12	40.50	2.06	2.81	24.00	44.20	21,400
939 00716	1-3/4 x 18	4.62	2.38	37.38	2.60	3.38	18.00	53.80	28,000
939 00731	1-3/4 x 24	4.62	2.38	43.38	2.60	3.38	24.00	61.00	28,000
939 00746	2 x 24	5.75	2.69	48.62	2.62	3.69	24.00	91.00	37,000
939 00761	2-1/2 x 24	6.50	3.12	51.80	3.06	4.44	24.00	150.00	60,000
939 00776	2-3/4 x 24	7.00	3.25	53.88	3.68	4.19	24.00	195.00	75,000

\*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL **1-800-727-0665** TO PLACE AN ORDER  
[www.induscowirerope.com](http://www.induscowirerope.com)

**⚠ WARNING** Never exceed working load limit.

See pages 4 - 10 for important safety information.  
 All measurements/units listed are in inches/pounds unless otherwise noted.