


POWER STRAND WIRE ROPE

ROTATION RESISTANT 19 x 7 CLASS BRIGHT IWRC

- The 19 x 7 rotation resistant wire rope has been developed for services where a minimum rotation or spinning of the rope is highly desirable. It is particularly applicable for the lifting or lowering of free loads with single part line only.
- Meets design requirements according to Federal Specification RR-W-410.

19 x 7 BIWRC

			
Indusco Part #	Diameter	Weight per Foot	Working Load Limit*
IMPROVED PLOW STEEL			
989 00126	1/4	.12	1,000
989 00201	5/16	.18	1,560
989 00276	3/8	.25	2,240
989 00346	7/16	.35	3,030
989 00446	1/2	.45	3,940
989 00536	9/16	.58	4,960
989 00626	5/8	.71	6,120
989 00712	3/4	1.02	8,720
EXTRA IMPROVED PLOW STEEL			
989 00126	1/4	.12	1,090
989 00203	5/16	.18	1,720
989 00278	3/8	.25	2,440
989 00348	7/16	.35	3,320
989 00448	1/2	.45	4,320
989 00537	9/16	.58	5,440
989 00626	5/8	.71	6,720
989 00712	3/4	1.02	9,600
989 00793	7/8	1.39	13,000
989 00868	1	1.82	16,800

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.