


POWER STRAND WIRE ROPE

CABLE LAID 7 x 7 x 7 AND 7 x 7 x 19 GALVANIZED

- Used for making very flexible wire rope slings.




Indusco Part #	Diameter	Construction	Weight per Foot	Working Load Limit*
989 00143	1/4 (9/32)	7x7x7	.11	1,300
989 00291	3/8	7x7x7	.21	2,220
989 00466	1/2	7x7x7	.37	3,820
989 00641	5/8	7x7x7	.58	5,840
989 00728	3/4	7x7x19	.88	8,560
989 00808	7/8	7x7x19	1.19	11,980
989 00882	1	7x7x19	1.56	15,700

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

1 x 7 GALVANIZED STEEL GUY WIRE EXTRA HIGH STRENGTH

- Used for standing rigging.
- Left lay.
- Meets design requirements per ASTM A475-Class-A.



Indusco Part #	Diameter	Construction	Weight per Foot	Working Load Limit*
989 00146	1/4	1X7	.12	1,330
989 00216	5/16	1X7	.21	2,240
989 00296	3/8	1X7	.28	3,080
989 00361	7/16	1X7	.36	4,160
989 00409	1/2	1X7	.54	5,380

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.