


STAINLESS STEEL WIRE ROPE SLEEVES

⚠ WARNING

- **NOT FOR LIFTING**
- Available in a range of finishes and sizes ranging from 1/32" to 5/8".
- When properly applied, hourglass sleeves are capable of supporting 90% of load strength of cable to which they are attached.

| Indusco Part # | Trade Size | A | B | C | Weight Per 100 pieces (Approximate) |
|-------------------------------------|------------|-----|-----|------|-------------------------------------|
| STAINLESS STEEL (OVAL SHAPE) | | | | | |
| 776 00401 | 1/16 | .13 | .21 | .38 | .15 |
| 776 00396 | 3/32 | .18 | .30 | .38 | .20 |
| 776 00389 | 1/8 | .23 | .36 | .38 | .40 |
| 776 00390 | 3/16 | .35 | .56 | .98 | 2.00 |
| 776 00391 | 1/4 | .45 | .71 | 1.14 | 4.50 |




WIRE ROPE STOPS

⚠ WARNING

- **NOT FOR LIFTING.**
- When properly attached, stop sleeves are capable of holding only 1/3 of the load strength of the cable to which they are attached.

| Indusco Part # | Trade Size | A | B | Weight Per 100 pieces (Approximate) |
|-----------------|------------|-----|-----|-------------------------------------|
| ALUMINUM | | | | |
| 838 00091 | 1/16 | .25 | .16 | .06 |
| 838 00096 | 3/32 | .34 | .31 | .23 |
| 838 00101 | 1/8 | .34 | .31 | .21 |
| 838 00106 | 5/32 | .44 | .34 | .37 |
| 838 00111 | 3/16 | .44 | .34 | .35 |
| 838 00116 | 1/4 | .69 | .69 | 2.10 |
| 838 00121 | 5/16 | .69 | .69 | 5.00 |
| COPPER | | | | |
| 838 00002 | 1/32 | .13 | .20 | .08 |
| 838 00001 | 1/16 | .25 | .16 | .19 |
| 838 00006 | 3/32 | .34 | .31 | .78 |
| 838 00011 | 1/8 | .34 | .31 | .71 |
| 838 00016 | 5/32 | .44 | .34 | 1.18 |
| 838 00021 | 3/16 | .44 | .34 | 1.06 |
| 838 00026 | 1/4 | .69 | .69 | 6.20 |
| 838 00031 | 5/16 | .69 | .69 | 5.30 |



⚠ WARNING Never exceed working load limit.

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.