















## GRADE 80 CHAIN SLING WORKING LOAD LIMITS

Grade 80 Alloy Chain Size								
Inches	MM	Single Leg	Double Leg			Triple & Quad Leg		
7/32	6	2,500	3,600	3,000	2,500	6,500	5,300	3,750
1/4 (9/32)	7	3,500	6,100	4,900	3,500	9,100	7,400	5,200
5/16	8	4,500	7,800	6,400	4,500	11,700	9,500	6,800
3/8	10	7,100	12,300	10,000	7,100	18,400	15,100	10,600
1/2	13	12,000	20,800	17,000	12,000	31,200	25,500	18,000
5/8	16	18,100	31,300	25,600	18,100	47,000	38,400	27,100
3/4	20	28,300	49,000	40,000	28,300	73,500	60,000	42,400
7/8	22	34,200	59,200	48,400	34,200	88,900	72,500	52,300
1	26	47,700	82,600	67,400	47,700	123,900	101,200	71,500
1-1/4	32	72,300	125,200	102,200	72,300	187,800	153,400	108,400

RATED CAPACITY BASED ON DESIGN FACTOR 4:1

## GRADE 100 CHAIN SLING WORKING LOAD LIMITS

Grade 100 Alloy Chain Size								
Inches	MM	Single Leg	Double Leg			Triple & Quad Leg		
-	6	3,200	5,500	4,500	3,200	8,300	6,800	4,800
1/4 (9/32)	7	4,300	7,400	6,100	4,300	11,200	9,100	6,400
5/16	8	5,700	9,900	8,100	5,700	14,800	12,100	8,500
3/8	10	8,800	15,200	12,400	8,800	22,900	18,700	13,200
1/2	13	15,000	26,000	21,200	15,000	39,000	31,800	22,500
5/8	16	22,600	39,100	32,000	22,600	58,700	47,900	33,900
3/4	20	35,300	61,100	49,900	35,300	91,700	74,900	52,950
7/8	22	42,700	74,000	60,400	42,700	110,900	90,600	64,000
1	26	59,700	103,400	84,400	59,700	155,100	126,000	89,550
1-1/4	32	90,400	156,600	127,800	90,400	234,900	191,700	135,600

RATED CAPACITY BASED ON DESIGN FACTOR 4:1

CALL **1-800-727-0665** TO PLACE AN ORDER  
[www.induscowirerope.com](http://www.induscowirerope.com)

**⚠ WARNING** Never exceed working load limit.

See pages 4 - 10 for important safety information.  
 All measurements/units listed are in inches/pounds unless otherwise noted.