


SYNTHETIC ROPE - THREE STRAND

⚠ WARNING

- Never exceed the working load limit of rope.
- Attachments must have at least same working load limit as the rope used.
- Keep out from under a raised load.
- Destroy, rather than discard, rope to be retired.
- Inspect rope frequently; store properly.
- Avoid overheating, shock loads, chemicals, rust and abrasion.
- Always destroy any product that shows wear, tearing or knots!



POLYPROPYLENE - YELLOW				
Indusco Part #	Size	Ft./Reel or Coil	Working Load Limit	Weight per 600'
721 00251	1/4	600/RL	110	6.5
721 00261	5/16	600/RL	170	11
721 00286	3/8	600/RL	240	17.5
721 00306	1/2	600/RL	420	28
721 00321	5/8	600/RL	695	45
721 00331	3/4	600/RL	1,090	64
721 00341	7/8	600/COIL	1,475	90
721 00346	1	600/COIL	1,830	107
NYLON - WHITE				
Indusco Part #	Size	Ft./Reel or Coil	Working Load Limit	Weight per 600'
721 00436	1/4	600/RL	145	9
721 00446	5/16	600/RL	230	15
721 00461	3/8	600/RL	320	21
721 00481	1/2	600/RL	630	39
721 00491	5/8	600/RL	1,110	63
721 00501	3/4	600/RL	1,825	86
721 00511	7/8	600/Coil	2,468	119
721 00516	1	600/Coil	3,175	156
COMBO - WHITE				
Indusco Part #	Size	Ft./Reel or Coil	Working Load Limit	Weight per 600'
721 00381	1/2	600	490	39
721 00391	5/8	600	760	55
721 00401	3/4	600	1,200	75
721 00406	1	600	1,880	131
1200' COILS & LARGER SIZES AVAILABLE UPON REQUEST				

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.