


MALLEABLE CLIPS - ZINC PLATED



⚠ WARNING

- **Not for Overhead Lifting!**
- Intended for use in making eye termination in right regular lay wire rope. Such an assembly is for non-critical light duty use where a small applied load is expected. For this reason, an efficiency of the termination is not stated.
- Cast iron base.
- Steel U-bolt and nuts.

ZINC PLATED - BULK						
Indusco Part #	Trade Size	Min. Number of Clips per Eye	Amount of Rope to Turn Back in Inches	Required Torque Ft. Lbs.	Bulk Packed	Weight Each
252 00081	1/16	2	4-3/4	1.5	500/BX	.02
252 00086	1/8	3	4-3/4	3.0	500/BX	.04
252 00091	3/16	3	5-1/2	4.5	500/BX	.08
252 00096	1/4	3	7	15	250/BX	.12
252 00101	5/16	3	7-3/4	15	250/BX	.15
252 00106	3/8	3	9-1/2	30	250/BX	.22
252 00111	7/16	3	10-1/4	40	100/BX	.33
252 00116	1/2	4	15-1/4	45	100/BX	.37
252 00121	9/16	4	16	50	100/BG	.59
252 00126	5/8	4	16	75	100/BG	.58
252 00131	3/4	5	22-1/4	75	100/BG	.84
252 00136	7/8	5	23-1/2	130	50/BG	1.25
252 00141	1	6	31	130	40/BG	1.56
252 00146	1-1/8	7	39-1/2	200	10/BG	2.50
252 00147	1-1/4	8	50	200	10/BG	3.15
252 00148	1-3/8	8	50	360	10/BG	4.45
252 00149	1-1/2	9	60-1/2	360	10/BG	5.20
ZINC PLATED - BOXED QTY						
252 00151	1/16	2	4-3/4	1.5	25/BX	.02
252 00156	1/8	3	4-3/4	3.0	25/BX	.04
252 00161	3/16	3	5-1/2	4.5	25/BX	.08
252 00166	1/4	3	7	15	25/BX	.12
252 00171	5/16	3	7-3/4	15	25/BX	.15
252 00176	3/8	3	9-1/2	30	25/BX	.22
252 00181	7/16	3	10-1/4	40	25/BX	.33
252 00186	1/2	4	15-1/4	75	25/BX	.37
252 00191	5/8	4	16	75	10/BX	.59
252 00196	3/4	5	22-1/4	75	10/BX	.84

WEIGHTS AND DIMENSIONS MAY VARY DUE TO MANUFACTURER TOLERANCES

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.