


DOUBLE GRIP CLIPS

⚠ WARNING

- **Not for Overhead Lifting!**
- Drop forged.
- Hot dipped galvanized.
- Intended for use in making eye termination in right regular lay wire rope.
- The efficiency rating of a properly prepared termination for clip sizes 3/16" through 7/8" is 80%, sizes 1" through 1-1/2" is 90%. This rating is based on the catalog breaking strength of the wire rope.
- Performance requirements FF-C-450D.
- Follow all warnings and instructions as supplied by the manufacturer.
- See Warning "**Double Grip Clips**" on Page 9 for proper use and selection.



Indusco Part #	Trade Size	Min. Number of Clips per Eye	Amount of Rope to Turn Back in Inches	Required Torque Ft. Lbs.	Weight Each
HOT DIPPED GALVANIZED					
252 00406	1/4	2	4	30	.18
252 00411	5/16	2	5	30	.28
252 00416	3/8	2	5-1/4	45	.40
252 00421	1/2	3	11	65	.70
252 00426	5/8	3	13-1/2	130	1.00
252 00431	3/4	3	16	225	1.75
252 00436	7/8	4	26	225	2.25
252 00441	1	5	37	225	3.00
252 00587	1-1/8	5	41	360	4.00
252 00271	1-1/4	6	55	360	4.60
252 00281	1-1/2	7	78	500	5.44

WEIGHTS AND DIMENSIONS MAY VARY DUE TO MANUFACTURER TOLERANCES

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.