


DROP FORGED CLIPS



- Drop forged.
- Hot dipped galvanized.
- For Right Regular Lay or Right Lang Lay wire only.
- The efficiency rating of a properly prepared termination for clip sizes 1/8" through 7/8" is 80%, sizes 1" through 2-3/4" is 90%. Rating is based on the catalog breaking strength of the wire rope.
- Performance requirements FF-C-450D.
- Follow all warnings and instructions as supplied by the manufacturer.

Indusco Part #	Trade Size	Min. Number of Clips per Eye	Amount of Rope to Turn Back in Inches	Required Torque Ft. Lbs.	Weight Each
HOT DIPPED GALVANIZED					
252 00206	1/8	2	3-1/4	4.5	.06
252 00211	3/16	2	3-3/4	7.5	.10
252 00216	1/4	2	4-3/4	15	.20
252 00221	5/16	2	5-1/4	30	.30
252 00226	3/8	2	6-1/2	45	.47
252 00231	7/16	2	7	65	.76
252 00236	1/2	3	11-1/2	65	.80
252 00241	9/16	3	12	95	1.04
252 00246	5/8	3	12	95	1.06
252 00251	3/4	3	18	130	1.50
252 00256	7/8	4	19	225	2.12
252 00261	1	5	26	225	2.60
252 00266	1-1/8	6	34	225	2.90
252 00271	1-1/4	7	44	360	4.30
252 00276	1-3/8	7	44	360	4.60
252 00281	1-1/2	8	54	360	5.40
252 00376	1-5/8	8	58	430	7.30
252 00286	1-3/4	8	61	590	9.25
252 00291	2	8	71	750	13.00
252 00516	2-1/4	8	73	750	16.00
252 00521	2-1/2	9	84	750	19.00

WEIGHTS AND DIMENSIONS MAY VARY DUE TO MANUFACTURER TOLERANCES

CALL 1-800-727-0665 TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.