


REGULAR THIMBLES

- For light duty applications and load conditions.
- Meets dimensional requirements of Federal Specifications FF-T-276B Type II.
- See Warnings “Thimbles” on Page 7 for proper use and selection.



Indusco Part #	Trade Size	A	B	C	D	Max Pin Dia.	Weight Each
HOT DIPPED GALVANIZED							
897 00146	1/8	1.93	1.06	1.31	.68	.62	.03
897 00151	3/16	1.93	1.06	1.31	.68	.62	.03
897 00156	1/4	1.96	1.06	1.31	.68	.62	.04
897 00161	5/16	2.12	1.25	1.50	.81	.75	.04
897 00166	3/8	2.37	1.46	1.62	.93	.75	.06
897 00176	1/2	2.75	1.75	1.87	1.12	1.06	.13
897 00181	5/8	3.50	2.37	2.25	1.37	1.25	.35
897 00186	3/4	3.75	2.68	2.50	1.62	1.50	.50
897 00191	7/8	5.00	3.18	3.50	1.87	1.75	.85
897 00196	1	5.68	3.75	4.25	2.50	2.37	1.00
897 00201	1-1/8 to 1-1/4	6.25	4.31	4.50	2.75	2.62	1.75
STAINLESS STEEL (TYPE 316)							
897 00131	1/4	1.96	1.06	1.31	.68	.62	.03
897 00134	5/16	2.12	1.25	1.50	.81	.75	.04
897 00136	3/8	2.37	1.46	1.62	.93	.75	.06
897 00141	1/2	2.75	1.75	1.87	1.12	1.06	.13
897 00143	5/8	3.50	2.37	2.25	1.37	1.25	.35

WEIGHTS AND DIMENSIONS MAY VARY DUE TO MANUFACTURER TOLERANCES

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.