


ROUND PIN CHAIN SHACKLES



- Drop forged.
- Hot dipped galvanized.
- Meets design requirements of Federal Specification RR-C-271 Type IV B Grade A Class 1.
- See Warnings “**Shackles**” on Page 7 for proper use and selection.

Indusco Part #	A Nominal Size	B Pin Dia.	C	D	F	Weight Each	Working Load Limit*
751 99999	1/4	.32	.88	.47	.69	.10	1,000
751 01042	5/16	.38	1.00	.53	.81	.19	1,500
751 01126	3/8	.44	1.25	.66	.97	.28	2,000
751 01044	7/16	.50	1.50	.72	1.13	.40	3,000
751 99999	1/2	.63	1.69	.81	1.31	.50	4,000
751 01111	5/8	.75	2.00	1.06	1.56	1.20	6,500
751 99999	3/4	.88	2.31	1.25	1.88	2.00	9,500
751 01116	7/8	1.00	2.81	1.44	2.13	3.50	13,000
751 99999	1	1.13	3.25	1.69	2.38	4.70	17,000
751 01046	1-1/8	1.25	3.50	1.81	2.75	6.80	19,000
751 99999	1-1/4	1.38	3.69	2.00	3.00	9.00	24,000
751 99999	1-3/8	1.50	4.50	2.25	3.13	12.00	27,000
751 99999	1-1/2	1.63	5.00	2.38	3.50	16.00	34,000
751 99999	1-3/4	2.00	5.88	2.88	4.00	30.00	50,000
751 01121	2	2.25	6.75	3.25	4.88	42.00	70,000

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.