


ALLOY MASTER LINKS - GRADE 80

- Painted finish.
- See Warnings “Master Links” on Page 7 for proper use and selection.

Indusco Part #	Diameter	Inside Length	Inside Width	Weight Each	Working Load Limit*
544 00266	1/2	5.00	2.50	.89	7,400
544 00271	5/8	5.50	2.75	1.60	9,000
544 00276	3/4	6.00	3.00	2.30	12,300
544 00281	1	7.00	3.50	4.75	26,000
544 00286	1-1/4	8.75	4.37	9.80	39,100
544 00291	1-1/2	10.50	5.25	17.20	61,000
544 00296	1-3/4	12.00	6.00	26.20	84,900
544 00301	2	14.00	7.00	41.20	102,600
544 00306	2-1/4	16.00	8.00	55.00	143,100
544 00311	2-1/2	16.00	8.00	71.60	160,000
544 99999	2-3/4	16.00	9.50	87.70	216,900
544 99999	3	18.00	9.00	115.00	228,000
544 99999	3-1/4	20.00	10.00	145.80	262,200
544 99999	3-1/2	24.00	12.00	200.00	279,000

* WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1 FOR WIRE ROPE SLINGS AND A DESIGN FACTOR OF 4:1 FOR GRADE 80 CHAIN SLINGS

WELDLESS END LINKS



⚠ WARNING

- NOT FOR LIFTING.
- Drop forged.
- Available as self colored or hot dipped galvanized.

Indusco Part #	Diameter Stock	Inside Length	Inside Width	Weight Each	Working Load Limit* (Single Pull)
544 03012	5/16	1.75	.50	.15	2,500
544 03014	3/8	1.87	.56	.23	3,800
544 03016	1/2	2.37	.75	.45	6,500
544 03018	5/8	3.25	1.00	.95	9,300
544 03020	3/4	3.50	1.12	1.51	14,000
544 99999	7/8	5.12	2.00	2.75	12,000
544 99999	1	5.75	2.25	3.95	15,200
544 99999	1-1/4	7.00	2.50	7.30	26,400
544 03022	1-3/8	7.75	2.75	10.38	30,000

* WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL 1-800-727-0665 TO PLACE AN ORDER
www.induscowirerope.com

⚠ **WARNING** Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.