



RAPID LINKS

⚠ WARNING

- NOT FOR LIFTING.
- Available zinc plated or stainless steel.
- See Warnings “Proof Coil Connecting Links” on Page 9 for proper use and selection.

Indusco Part #	Size	A	B	C	D	Weight Per 100 pcs.	Working Load Limit*
STANDARD ZINC PLATED							
544 00392	1/8	1.44	1.13	.38	.18	2	130
544 00397	3/16	2.00	1.56	.50	.25	5	400
544 00402	1/4	2.38	1.88	.56	.31	8	600
544 00412	5/16	2.96	2.31	.67	.38	18	800
544 00417	3/8	3.13	2.50	.75	.44	25	1,200
544 00419	7/16	3.91	3.08	.85	.56	43	3,320
544 00421	1/2	4.18	3.18	.88	.61	54	4,500
STANDARD STAINLESS STEEL							
544 00476	1/8	1.44	1.13	.38	.18	2	220
544 00481	3/16	2.00	1.56	.50	.25	5	660
544 00486	1/4	2.38	1.88	.56	.31	8	880
544 00491	5/16	2.96	2.31	.67	.38	18	1,900
544 00496	3/8	3.13	2.50	.75	.44	25	2,300
544 00501	1/2	4.18	3.18	.88	.61	54	3,300
PREMIUM ZINC PLATED							
544 00391	1/8	1.44	1.13	.38	.18	2	400
544 00396	3/16	2.00	1.56	.50	.25	5	750
544 00401	1/4	2.38	1.88	.56	.31	8	1,250
544 00411	5/16	2.96	2.31	.67	.38	18	1,900
544 00416	3/8	3.13	2.50	.75	.44	25	2,650
544 00421	1/2	4.18	3.18	.88	.61	53	4,500
544 00466	9/16	4.75	3.66	1.06	.70	85	4,840
544 00471	5/8	5.50	3.91	1.18	.75	133	6,380

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 4:1

CALL **1-800-727-0665** TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.