



SWIVEL EYE HOOKS

- Drop forged.
- Intended for use as a positioning device and is not intended to rotate under load.
- See Warnings “**Hoist Hooks**” on Page 6 for proper use and selection.
- Follow all Warnings, Use and Application Instructions as supplied by the Manufacturer.

ALLOY STEEL SWIVEL EYE HOOKS*									
Indusco Part # With Latch	Working Load Limit (Tons)	DIMENSIONS							Weight Each
		A	B	C	D	E	F	M	
474 00936	1	.80	.38	4.50	.72	2.82	2.00	.90	.75
474 00941	1-1/2	1.30	.50	5.39	.84	3.10	2.50	.90	1.25
474 00943	2	1.50	.63	6.10	1.00	3.50	3.00	1.00	2.25
474 00946	3	1.50	.63	6.50	1.12	3.96	3.00	1.10	2.50
474 00951	4-1/2	1.60	.75	7.50	1.45	4.80	3.50	1.35	4.90
474 00956	7	2.30	1.00	9.63	1.80	6.27	4.56	1.60	10.30
474 00961	11	2.53	1.13	11.36	2.25	7.45	5.00	2.08	19.50
474 00706	15	2.55	1.25	12.25	2.60	8.30	5.62	2.27	23.50
474 00707	22	3.76	1.50	16.70	3.00	10.30	7.10	3.00	47.00
CARBON STEEL SWIVEL EYE HOOKS**									
474 00966	3/4	.80	.38	4.50	.72	2.82	2.00	.90	.75
474 00971	1	1.30	.50	5.39	.84	3.10	2.50	.90	1.25
474 00976	1-1/2	1.50	.63	6.10	1.00	3.50	3.00	1.00	2.25
474 00978	2	1.50	.63	6.50	1.12	3.96	3.00	1.10	2.50
474 00981	3	1.60	.75	7.50	1.45	4.80	3.50	1.35	4.90
474 00986	5	2.30	1.00	9.63	1.80	6.27	4.56	1.60	10.30
474 00991	7-1/2	2.53	1.13	11.36	2.25	7.45	5.00	2.08	19.50
474 00464	10	2.55	1.25	12.25	2.60	8.30	5.62	2.27	23.50
474 99999	15	3.76	1.50	16.70	3.00	10.30	7.10	3.00	47.00

*WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 4:1

**WORKING LOAD LIMIT IS BASED ON A DESIGN FACTOR OF 5:1

CALL 1-800-727-0665 TO PLACE AN ORDER
www.induscowirerope.com

⚠ WARNING Never exceed working load limit.

See pages 4 - 10 for important safety information.
 All measurements/units listed are in inches/pounds unless otherwise noted.